

T5 Waterproof fixtures



- with Philips Electronic ballast, Polycarbonat housing and cover, metal clips



1x14W, 1x28W, 1x35W, 1x49W
(tubes not inclusive)

2x14W, 2x28W, 2x35W, 2x49W
(tubes not inclusive)

Exclusive Product for GC-Group in Germany

The whole housing of YH-series T5 waterproof fixture is made from polycarbonat with the feature of impact-resistant and fire-proof. The protection level is IP65.

Highlights:


- with ENEC certificate
- high quality Electronic ballast from Philips or Osram
- clips made of metal, instead of plastic
- cover and base made from polycarbonat



Philips ballast



Metal clip



5 connectors



ENEC certifikat-No. 69242588

Specification:

IP65; UV-proof; suitable for T5 fluorescent tube; socket G13; Ta: -15°C~50°C

Type	Wattage	Fixture dimension	Number Of metal clips	pcs/carton	carton-Dimension	G.W.
YH5114T (QFW14ELT)	1x14W	615x78x80 (mm, LxBxH)	4	20	635x360x340 (mm, LxBxH)	20,00kg
YH5128T (QFW28ELT)	1x28W	1215x78x80 (mm, LxBxH)	8	12	1240x270x275 (mm, LxBxH)	20,00kg
YH5135T (QFW35ELT)	1x35W	1515x78x80 (mm, LxBxH)	12	9	1540x270x210 (mm, LxBxH)	18,50kg
YH5149T (QFW49ELT)	1x49W	1515x78x80 (mm, LxBxH)	12	9	1540x270x210 (mm, LxBxH)	18,50kg
YH5214T (QFW214ELT)	2x14W	615x95x80 (mm, LxBxH)	6	15	635x320x340 (mm, LxBxH)	16,80kg
YH5228T (QFW228ELT)	2x28W	1215x95x80 (mm, LxBxH)	10	9	1240x320x210 (mm, LxBxH)	17,00kg
YH5235T (QFW235ELT)	2x35W	1515x95x80 (mm, LxBxH)	12	6	1540x210x210 (mm, LxBxH)	14,50kg
YH5249T (QFW249ELT)	2x49W	1515x95x80 (mm, LxBxH)	12	6	1540x210x210 (mm, LxBxH)	14,50kg